

MATERIAL SAFETY DATA SHEET
物质安全资料表

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION 产品和公司资料

PRODUCT NAME: Prepreg (S0401 150)

产品名称: 半固化片(S0401 150)

PRODUCT USE: Substrate for printed circuitry

用途: 用于制作印制电路板

NAME of COMPANY and ADDRESS: SHENGYI TECHNOLOGY CO., LTD.

No.5 Western Industry Road North Industry District,Dongguan SSL
Sci.&Tech.Industry Park,Dongguan City,Guangdong ,P.R.China

公司名称及地址: 广东生益科技股份有限公司;

中国广东省东莞市松山湖科技产业园区北部工业园工业西路5号

FOR MORE INFORMATION CALL:

紧急联络电话: (Monday-Friday, 8:00am-5:00pm)

(0769)22271828(万江)\ 22899388(松山湖)

IN CASE OF EMERGENCY CALL:

(24 Hours/Day, 7 Days/Week)

(0769)22271828(万江)\ 22899388(松山湖)

2.HAZARDS IDENTIFICATION 危害性资料

EMERGENCY OVERVIEW:

紧急情况概述:

A nonflammable, sheet material. Dust, when machined or punched may cause skin or eye irritation. Fumes, if decomposed may irritate eyes, nose, and throat.

是一种难燃的材料。当使用或打孔时可能产生粉末,可能使皮肤或眼睛感到刺激。当分解时产生的气体会刺激眼睛、鼻和咽喉。

POTENTIAL HEALTH HAZARDS:

潜在的危害健康的危险:

SKIN: Dust may cause moderate skin irritation.

皮肤: 粉末将导致中等程度皮肤过敏。

EYES: Dust may cause moderate eye irritation. Fumes may irritate eyes.

眼睛: 粉末将导致中等程度眼睛过敏。

INHALATION: Fibrous glass dust may be released from the fiber-glass cloth substrate when machined.

吸入物: 当使用玻璃布时玻璃纤维粉末可能会飞散出。

INGESTION: Not determined.

摄食: 没有参考值。

DELAYED EFFECTS: Our product is reinforced with continuous filament fiber glass. Dust generated from the cutting, grinding, machining, etc., would not be expected to produce respirable particles.IARC considers continuous filaments as unclassifiable or probably non-carcinogenic.

慢性影响: 我们的产品用的是加强型连续的玻璃纤维丝。当切割、打孔加工时不会产生可吸入的颗粒。IARC组织没有将连续型玻璃纤维丝列入致癌目录。

3. COMPOSITION/INFORMATION ON INGREDIENTS 组成成份资料

INGREDIENT NAME	CAS #	WEIGHT %
成分名称	化学文摘号	重量比
Continuous Filament Fiber Glass 玻纤布	(65997-17-3)	25-61
Brominated Epoxy Resin 溴化环氧树脂	(26265-08-7)	39-75

4. FIRST AID MEASURES 首要援助措施

SKIN: Wash in flowing water or shower. Remove contaminated clothing.

皮肤: 脱下已污染衣服,用流动水冲洗。

EYE: Irrigate with flowing water for 15 minutes. If irritation persists, consult a physician.

眼睛: 用流动水冲洗15分钟,如过敏现象持续发生,请求助于医生。

INHALATION: If overcome by dust or smoke, move to fresh air. If not breathing, give mouth-to-mouth resuscitation. Call physician.

吸入：如粉末烟尘太多请转移到有新鲜空气的地方，如没有呼吸，请进行人工呼吸。并致电医生。

INGESTION: If large amounts are ingested, consult physician.

摄食：如吸入大量，请致电医生。

ADVICE TO PHYSICIAN: Treat symptomatically

建议医生：处理出现的症状。

5. FIRE FIGHTING MEASURES 火灾测试

FLAMMABLE PROPERTIES: N/A

易燃烧性：不适用

FLASH POINT: N/A

闪点：不适用

FLASH POINT METHOD: N/A

闪点方式：不适用

AUTOIGNITION TEMPERATURE: Not determined

自燃点温度：无规定

UPPER FLAME LIMIT (Volume % in air): N/A

燃烧上限：不适用

LOWER FLAME LIMIT (Volume % in air): N/A

燃烧下限：不适用

FLAME PROPAGATION RATE (Solids): UL V-O

燃烧等级：UL V-O

OSHA FLAMMABILITY CLASS: N/A

OSHA 燃烧级别：不适用

EXTINGUISHING MEDIA: Water, CO2 and dry chemical

灭火介质：水、CO2及干化学品

UNUSUAL FIRE AND EXPLOSION HAZARDS: May give off toxic hydrogen bromide when thermally decomposed.

不正常火灾及爆炸危险：当发生热分解时可能会释放出有毒的溴化氢。

SPECIAL FIREFIGHTING PRECAUTIONS/INSTRUCTIONS:

特别火灾指导：

Firemen should wear proper protective equipment and positive pressure self-contained breathing apparatus.

消防员须身穿保护装置及正压呼吸设施。

6. ACCIDENTAL RELEASE MEASURES 意外事故的应变措施

IN CASE OF SPILL OR OTHER RELEASE: (Always wear recommended personal protection equipment)

如有泄漏或其他释放：(通常身穿所推荐的保护设施)

Not applicable, material is an article.

不适用于固体材料。

Spills and releases may have to be reported to local authorities.

有关泄漏应报告当地政府。

7. HANDLING AND STORAGE 仓储指南

NORMAL HANDLING: (Always wear recommended personal protective equipment.)

规范指南：(建议穿戴个人防护设施)

The primary exposure route is inhalation of dust when from fumes or vapors when heated.

主要是预防暴露部位吸入当冒烟、气化液体受热时所产生的粉尘。

STORAGE RECOMMENDATIONS: N/A

贮存建议：不适用。

8. EXPOSURE CONTROLS/PERSONAL PROTECTION 泄漏控制/个人防护

ENGINEERING CONTROLS: Use local exhaust ventilation to control dust.

工程控制：使用当地除尘通风设施。

PERSONAL PROTECTIVE EQUIPMENT:

个人防护措施:

SKIN PROTECTION: For brief contact to dust, no precautions other than clean body-covering clothing should be needed. Use gloves and aprons when prolonged or frequently repeated contact occurs.

皮肤保护: 对于短暂性的接触粉尘, 需要时清洗身体或衣服, 无预防措施。对于长期性的接触, 要配带手套和围裙

EYE PROTECTION: Use appropriate eye protection when machining material.

眼睛保护: 当加工材料时使用眼睛保护装置。

RESPIRATORY PROTECTION: When respiratory protection is required for certain operations, use a NIOSH-approved dust respirator.

呼吸保护: 当进行产生大量粉尘的操作时使用规范的粉尘防毒面罩。

ADDITIONAL RECOMMENDATIONS: N/A

其它建议: 不适用

9. PHYSICAL AND CHEMICAL PROPERTIES 物理化学性能

APPEARANCE: Yellow to amber sheets

外观: 黄色

PHYSICAL STATE: Solid

物理形态: 固体

ODOR: None, unless heated

气味: 无味, 除非加热

SPECIFIC GRAVITY: (Water = 1.0) 1.5 +/- 0.25

比重: (水=1.0) 1.5 +/- 0.25

SOLUBILITY IN WATER: (Weight %) Negligible in water

水溶性: (重量%) 在水中可忽略

10. STABILITY AND REACTIVITY 稳定性及反应性

NORMALLY STABLE? (conditions to avoid) Stable

通常稳定? 稳定

INCOMPATIBILITIES: Not determined

不兼容性: 不确定

HAZARDOUS DECOMPOSITION PRODUCTS: CO, CO₂, HBr, Oxides of nitrogen if heated in excess of 300 deg. C.

危险的腐化产品: CO, CO₂, HBr, NO_x (当加热超过300℃)。

HAZARDOUS POLYMERIZATION? None

危险聚合物? 无

11. TOXICOLOGICAL INFORMATION 毒物学的资料

IMMEDIATE (ACUTE) EFFECTS: Dust may cause moderate eye, skin and respiratory irritation.

敏感反应: 灰尘将导致眼、皮肤中度过敏。

DELAYED (SUBCHRONIC & CHRONIC) EFFECTS: NTP has determined that respirable size glasswool may be reasonably anticipated to be a carcinogen. IARC has also classified glasswool as a possible carcinogen. Our product is reinforced with continuous filament fiber glass. Dust generated from the cutting, grinding, machining, etc., would not be expected to produce respirable particles. IARC considers continuous glass filaments as unclassifiable or probably non-carcinogenic.

慢性反应: NTP组织认为悬浮性的玻璃棉颗粒理论上可致癌。IARC组织也将玻璃棉列为致癌物。我们的产品是加强型的连续玻璃纤维丝产品。当切割、研磨、制造时通常不会产生吸入性颗粒。IARC组织认为连续型玻璃纤维丝不会致癌。

12. ECOLOGICAL INFORMATION 生态学资料

Not Biodegradable

非生物降解。

13. DISPOSAL CONSIDERATIONS 处置问题

Is the unused product a hazardous waste substances list of country hazardous waste if discarded? No
列入国家危险废物名录的危险废物不能够再利用时是否被丢弃? 不

OTHER DISPOSAL CONSIDERATIONS: Disposal must be made in accordance with all applicable Local regulations.

其它处置问题：处置必须遵循当地的法律法规。

Suggestion method after products will be discarded:

1. Incineration method: incinerate the unused products, this method may produce some brominated compound gas.
2. Bury into deep earth.

产品报废之后有以下几种处置方法：

1. 焚烧法，焚烧过程中可能产生有毒的溴化物气体；
2. 填埋法。

14. TRANSPORT INFORMATION 运输资料

For additional information on shipping regulations affecting this material, contact the information number found on the first page.

附带资料是当运输规则影响到物料时，请和第一页所提供的联系方式联系。

15. REGULATORY INFORMATION 法规资料

HAZARDOUS WASTE SUBSTANCES LIST OF COUNTRY: 国家危险废物名录

The resin system components listed in the hazardous waste substances list of country (HW13). 环氧化合物类被列入国家危险废物名录当中 (HW13)。

ADDITIONAL REGULATORY INFORMATION:

附加法规资料：

SHENGYI TECHNOLOGY CO., LTD. does not use polybromide-biphenyls or polybromide-biphenyloxides as a fire retardant in any of our epoxy resin systems.

广东生益科技股份有限公司没有采用多溴联苯或多溴联苯基氧化物作为阻燃剂在产品的环氧树脂体系当中。

16. OTHER INFORMATION 其它资料

CURRENT ISSUE DATE: 21/03/2018

现在版本日期：21/03/2018

PREVIOUS ISSUE DATE: 22/12/2005

首次版本日期：22/12/2005

CHANGES TO MSDS FROM PREVIOUS ISSUE DATA ARE DUE TO THE FOLLOWING:

变更MSDS基于以下原因：

Reviewed and re-issued for other relatively requirement.

重新修订是由于相关的要求所使。